# **RODDER**

JAMESON.

**FOR 2-4" CONDUIT** 

Jameson offers a comprehensive Good Buddy® family to meet various applications for 3/8" rod: Manhole-to-riser, riser-to-riser, cable vaults and large conduit runs.

- Recommended For Use In 2"-4" Conduit
- .250 Core 3/8 OD Rod
- 7" Bending Radius
- 1,000-lb Tensile/Pull Strength
- · Accessory Kit, End Ferrule and Pulling Eye Included





300' - 400'



**GOOD BUDDY®II** 

400' - 600'



**GOOD BUDDY®III** 

300' - 400'

Part Number	Replacement Reel	Description
9-25-300M	9-300RRM	300' X 3/8" Good Buddy
9-25-400M	9-400RRM	400' X 3/8" Good Buddy
11A-25-400M	11A-400RRM	400' X 3/8" Good Buddy II
11A-25-500M	11A-500RRM	500' X 3/8" Good Buddy II
11A-25-600M	11A-600RRM	600' X 3/8" Good Buddy II
9A-25-300M	9-300RRM	300' X 3/8" Good Buddy III
9A-25-400M	9-400RRM	400' X 3/8" Good Buddy III

All Good Buddy® conduit rodder models come standard with rod marked in 5' increments. Add 'MM' to part number for metric measure (1m increments).





# **ACCESSORY KIT**

Contents: Canvas Pouch, Swivel Pulling Eye, Splice Ferrule, End Ferrule, Adhesive, and Emery Cloth. Pouch attaches to Rodder Frame for Easy Access (Included With Rodder)



#### **GOOD BUDDY®**

#### 3/8" Diameter Rod - For Conduit 2-4" In Diameter

The Good Buddy® family meets various applications for 3/8" rod: Manhole-to-riser, riser-to-riser, cable vaults and large conduit runs.

- 7" Bending Radius
- Male end ferrule: #3/8"-16 thread pitch
- 1000-lb pull/tensile strength
- · Accessory Kit, End Ferrule and Pulling Eye Included



## **GOOD BUDDY® II**

### 3/8" Diameter Rod - Increased Length For Longer Runs

- 400', 500' and 600' lengths
- Oversized wheels support weight of longer rod
- Frame handle and wheels for transport
- · Friction brake and safety roller feed
- · Operates vertically or horizontally
- 1000-lb pull/tensile strength
- Dimensions: 40"H x 32"L x 18"W (106 x 81.3 x 45.7 cm)



#### **GOOD BUDDY® III**

#### 3/8" Diameter Rod - Smaller Frame For Maximum Portability

- 300' and 400' lengths
- Wheels and frame handle for transport
- Smaller frame size than GB or GB II
- Friction brake and safety roller feed
- · Operates vertically or horizontally
- 1000-lb pull/tensile strength
- Dimensions: 34"H x 26.5"L x 15.5"W (86.4 x 67.3 x 39.4 cm)

## RODDER ACCESSORIES



Repair Adhesive

Part Number	Accessories	Thread 3/8" - 16 UNC	
9-25-AK	Accessory Kit	End Ferrule, Splice Ferrule, Adhesive, Emery Cloth, Pouch	
9-139	Swivel Eye	Attach pull line or grip to freely rotating eye	
9-141	Roller Guide	Guides rod through bends, sweeps, misalignments, wires	
11-142	Shackle Fitting	Use with Swivel Eye for larger pulling loop to attach Pulling Eye. <b>Must use 11-139 Swivel Eye</b> .	
9-143	Swivel Coupling	Connect two rods when single length is not long enough; provides rotation when pulling line, wire or rope.	
9-148	Rod Grapples	Connects two rodders from opposite directions	
9-25-12ST	12" Stinger Tip	Guide rod through bends, sweeps, misalignments	
9-25-24ST	24" Stinger Tip		
9-140	Splice Repair Kit	Splice Ferrule, Adhesive, Emery Cloth, Instructions	
9-146	End Ferrule Repair	End Ferrule, Adhesive, Emery Cloth, Instructions	
11A-AWK	AT Wheel Kit	Replacement All-Terrain Wheel Kit for Good Buddy II only	

Big Buddy® Grapples